

southco

PROPRIETARY ITEM - EXCEPT FOR USES EXPRESSLY GRANTED IN WRITING INFORMATION DISCLOSED HEREON IS CONFIDENTIAL AND ALL RIGHTS PATENT AND OTHERWISE ARE RESERVED BY SOUTHCO, INC.


No. E3 PADLOCK BRACKET, TAB STYLE

DATE	DRAWN	CHKD	SCALE	DRAWING NUMBER
29MAY1998	MDM	KAE	1:1	J-E3-77-101

REV	DATE	DRAWN/CHKD	DESCRIPTION	PART NUMBER	MATERIAL	FINISH
G	17DEC2002	SCR/AJH	PRN: P2002-0805	E3-77-101-24	304 STAINLESS STEEL	PASSIVATED
				E3-77-101-31	304 STAINLESS STEEL	BLACK POWDER COATED
				E3-77-101-07	304 STAINLESS STEEL	BEIGE POWDER COATED
				E3-77-101-09	304 STAINLESS STEEL	SEE NOTE G

MILLIMETERS

ALL DIMENSIONS WITHOUT TOLERANCES ARE FOR REFERENCE ONLY.



THIRD ANGLE PROJECTION

A4 PAPER SIZE

NOTES:

- PADLOCK BRACKET IS TO BE USED WITH E3 SINGLE HOLE MOUNT, LARGE SIZE AND MINIMAL PROTRUSION VISE ACTION COMPRESSION LATCHES (EXCEPT KNOB AND T-HANDLE) OR E5 QUAD PANEL LATCH.
- WHEN CALCULATING TOOL GRIP, ADD PADLOCK THICKNESS TO PANEL (DOOR) THICKNESS.
- TO PROVIDE SEALING, USE TWO FLANGE GASKETS, ONE ON EACH SIDE OF PADLOCK BRACKET. ADD COMPRESSED THICKNESS OF EACH FLANGE GASKET TO THE PANEL (DOOR) THICKNESS.
- SOUTHCO'S LONGER SHANK KEYS ARE REQUIRED WHEN USED WITH THE PADLOCK BRACKET.
- MINIMUM PADLOCK SHACKLE CLEARANCE IS 38mm.
- PADLOCK BRACKET IS NOT RECOMENDED TO BE USED WITH A PULL TAB OR SEALING COVER.
- LUCENT MEDIUM GRAY POWDER COAT.

